

8160W DC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Trusted reliability and quiet operation.



KEY FEATURES

QUIET
OPERATION
DC Motor

WI-FI
Built In



myQ integrates with leading smart home platforms. Visit myQ.com to learn more.

RELIABLE

DC MOTOR IS PURPOSEFULLY DESIGNED FOR QUIET PERFORMANCE.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

SOFT START/STOP FOR SMOOTH OPERATION.

WARRANTY 4-YEAR MOTOR, 1-YEAR PARTS AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

SECURE

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

**MULTI-FUNCTION
CONTROL PANEL®**
Includes lockout controls and
accessory programmability.



882LMW

3-BUTTON REMOTE CONTROL
Operates up to 3 openers.



893LM

POWERFUL ADD-ONS:

myQ HOME BRIDGE
Adds Apple® HomeKit™ compatibility
and Siri® voice control to Wi-Fi-enabled
openers. Installs easily in the garage
within Wi-Fi range.*



819LMB

**MINI UNIVERSAL
REMOTE CONTROL**
Compact and portable to provide
quick, easy garage access.



374UT

*Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV® with tvOS™ 10.0 or later or an iPad® with iOS 10.0 or later set up as a home hub. Smartphone not included.

PRODUCT GUIDE 8160W

DC CHAIN DRIVE WI-FI
GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWF)



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

8.5"
Per second for door to move upward

SPEED

6.5"
Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: **~200'**

Operating Temperature: -30°F to 150°F
Frequency:

- Remote Controls: Security+ 2.0
- Garage Door Opener: Security+ 2.0
- Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0 ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO

902-928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers via smartphone or tablet.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 1 100-Watt Lightbulb
- Adjustable-Time Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)

18
HEAD

20
RAIL (7')

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)
- Garage Door Opener Head (8160W)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 myQ Devices



*WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.